


ZC68




技术参数/Technical info




力量级别/Power size	EN2	EN3	EN4
最大门宽(mm)/Width of door max(mm)	850	950	1100
最大门重(kg)/Weight of door max(kg)	40	60	80
产品重量(kg)/Weight of body(kg)	0. 785		
铁壳尺寸(mm)/Dimension of cement box(mm)	L218×W52×H42. 5		
使用寿命/Passed durability test	500,000次/500,000 cycles		
通过CE认证: 4 8 4 1 1 3 3 4 4 1 1 3 3 4 4 1 1 3 3 4 4 1 1 3 3 4 4 4 1 1 3 3 4 4 4 1 1 3 3 4 4 4 4	A		









- 1. 关门速度调节范围: 180°-10°
- 2. 闭门速度调节范围: 10°-0°
- 1. Closing speed adjustment range 180°-10°
- 2. Door closer speed adjustment tange 10°-0°

●Feature/特点

- -High quality imported gaskets to prevent oil leakage.
- (高品质进口垫圈防止漏油。)
- -Strong spring to guarantee powerful closing.
- (强力弹簧,闭门力度大。)
- -Side swing rocker for easy erection.
- (可偏摆摇臂,方便安装。)
- -Fine quality aluminium alloy body. Provided with 2 coatings for protection.
- (优质铝合金机体,两层光亮层保护。)
- -Full hydraulic control of closing speeds by the help of adjustable
- (全液压控制可调阀门关闭速度。)
- -2 speed controls: closing speed and latching speed.
- (两个调速阀独立控制两段闭门速度。)

